



Ess UPS System Solar Lithium Battery 24V 25.6V 100ah For Home Solar Energy Storage

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: XWELL
- Certification: UN38.3, MSDS, UL, CB, BIS, PSE, GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE
- Model Number: XW-LAR128100
- Minimum Order Quantity: 1 pcs
- Price: negotiable
- Packaging Details: Carton
- Delivery Time: 7-10 working days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 pcs per month



Product Specification

- Battery Capacity: 7AH 12AH 50AH 100AH 200AH
- Battery Energy: 89.6 -to2560WH
- Battery Max Charge Current: 7 - To 100A
- Battery Cell Type: Cylindrical Or Prismatic Type
- Configuration: 4S1P
- Nominal Voltage: 12.8V
- DC Resistance: $\leq 10\text{m}\Omega$
- Terminal Type: F1 Connector
- Cover Sealing Type: Screw / Gel Sealing Optional
- Waterproof: IP65
- Highlight: Solar Lithium Battery 24V,
Solar Lithium Battery 25.6V,
UPS lithium solar battery

Product Description

Battery Lithium 12V 12.8V 24V 25.6V 100ah For Home Solar Energy Storage System Ess UPS System

ESS Lithium Battery Features

1. Long service life
2. High reliability and good quality
3. Good deep discharge performance
4. Strong discharge recovery capability

ESS Lithium Battery Application fields

Control system, electric toys, emergency lights, electric tools, alarm system, Emergency lighting system, standby power supply, UPS, power system, Telecommunication equipment, fire protection and security system, railway system and power station, etc.

Lithium Battery Replacement Lead-Acid Specification

Model	12.8V7Ah	12.8V12Ah	12.8V50Ah	12.8V100Ah	12.8V200Ah
Nominal Voltage	12.8V				
Nominal Capacity @25C	7AH	12AH	50AH	100AH	200AH
Nominal Energy @25°C	89.6WH	153.6WH	640WH	1280WH	2560WH
Battery Cell Type	Cylinder		Prismatic 50Ah	Prismatic 100Ah	Prismatic 100Ah
Configuration (xSxP)	4S1P	4S2P	4S1P	4S1P	4S2P
Max. Continuous Charge Current @25°C	7A	12A	50A	100A	100A
Max. Continuous Discharge Current @25°C	7A	12A	50A	100A	100A
DC Resistance	≤10mΩ				
Full Charged Voltage	14.6V				
Discharge Cut-off Voltage	10V				
Operate Temperature Range	Charge: 0°C~55°C; Discharge: -20°C~60°C; Storage: -20°C~45°C				
Dimension (mm)	152x65x94mm	152x99.5x100mm	229x138x208mm	326x171x215mm	522x240x218mm
Weight (KG)	1.1KG	1.7KG	7KG	12.5KG	25KG
Terminal Type	F1 terminal		Screw terminal		
Cover Sealing type	Screw / gel sealing optional				
Waterproof	IP65				
Cycle life	100% DOD Cycles @ 25xC 1C/1C: >2000 times80% DOD Cycles @ 25C 1C/1C: >6000 times50% DoD Cycles @ 25C, 1C/1C: >5000 times				
LCD Screen Display	Optional (Show voltage V, Power %)				
Bluetooth	Optional (Bluetooth with mobile APP)				
Series and Parallels Function	Available to make in series and parallels to get 24V, 36V, 48V				
Heating Function	Optional, Suitable for cold area application				

Our Advantages

Professional Technical Team, Xwell's R&D technical team has received more than 20 invention and application patents.

Professional Sales Team, xwell possesses well-trained sales team which helps customers addressing difficulty meeting in battery or battery solution selecting.

Unique Pack Technique, xwell possesses special pack technique to better protect the battery and increase the life span of the battery pack.

Punctual Delivery, xwell has strict production plan to promise on time delivery.

Safety Certification Guarantee, Most products have been certified according to international standard including CE, MSDS, UN38.3, etc.

Perfect after Sales-service, xwell has a professional QC team which applies strict quality control on production and provide perfect after-sale service to customers



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

+86 18620492985

sales@esslithiumbattery.com

esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China